



PETROTM OIL

LUBENZ VISTA AUTOMATIC TRANSMISSION FLUID D VI

DESCRIPTION

LUBENZ VISTA AUTOMATIC TRANSMISSION FLUID D VI is formulated with premium synthetic base stocks and advanced additive technology, and meets all the stringent requirements of General Motors' DEXRON®-VI specification, which is designed for the modern automatic transmissions in GM vehicles. **LUBENZ VISTA AUTOMATIC TRANSMISSION FLUID D VI** can be used in new and old GM automatic transmissions & it is fully back-serviceable and can be used wherever DEXRON®-II and/or DEXRON®-III are recommended.

APPLICATIONS

LUBENZ VISTA AUTOMATIC TRANSMISSION FLUID D VI is high quality ATF suitable for use in automatic transmissions with torque converters of passenger cars, as well as in wet clutches and power steering units.

PRODUCT BENEFITS

- Optimized frictional properties that provide smooth gear shifting during low temperature operation and help prevent transmission vibration
- Extends transmission fluid life and prevents fluid breakdown at higher operating temperatures
- Improved oxidation and thermal stability
- Reduces sludge and varnish build-up
- Outstanding low temperature performance
- Maintains lubricity
- Thoroughly field tested
- Low viscosity formulation provides fuel economy benefits compared with fluids formulated to meet DEXRON®IIIH or earlier specifications.
- Improved anti-wear protection which contributes to extended transmission life
- Protects transmission gears and allows them to operate smoothly

RECOMMENDATIONS / SPECIFICATIONS

Meets or Exceeds General Motors DEXRON®-VI Requirements & for 2006 and newer GM vehicles.
Meets the performance requirements of MB 236.41, Allison C-4 & VOITH H55.6335xx.

TYPICAL TECHNICAL PROPERTIES	
Color, VISUAL	RED
Density at 15°C, g/ml, ASTM D4052	0.847
Kinematic Viscosity at 40°C, mm ² /s, ASTM D445	30.2
Kinematic Viscosity at 100°C, mm ² /s, ASTM D445	6.1
Viscosity Index, ASTM D2270	148
Flash Point(COC), °C, ASTM D92	208
Pour Point, °C, ASTM D97	-54
Brookfield viscosity at -40°C, mPa.s, ASTM D2983	11,000

Note: These characteristics are typical of current production. While future production will conform to LUBENZ VISTA AUTOMATIC TRANSMISSION FL, variations in these characteristics may occur.